


128 way Master Station

Designed to meet BS8893:2024



OCCPLS

OmniCALL is an addressable EVC (Emergency Voice Communication) system that enables disabled refuge, fire telephones, emergency/steward telephones and emergency assistance alarms to be connected in a single system.

OmniCALL

MAIN SYSTEM FEATURES

- Loop and radial outstation connection on the same system
- Loop connection
 - 2 core cabling
 - Non-polarity dependence
 - 32 outstations per loop
 - Max loop length 1.4km (Dependent on number of outstations).
 - No distance limitation between outstations
- Radial connection
 - 2 core cabling
 - Non-polarity dependence
 - Max radial length 1.4km shared between 4 outstations
- Same outstation for loop or radial connection
- Disabled Toilet Alarms/Assistance alarms connect direct to outstations
 - Each assistance call is a separate address
- Designed for BS5839-9 and BS8893 compliance


MASTER STATION FEATURES:

- Stainless steel finish
- Flexible outstation connection
 - Supports up to 128 outstations plus 128 assistance alarms
 - Multiple overdoor lights and reset points can be added
 - Assistance alarms have a separate indication on the master station
 - By fitting the three additional line cards, the system can support a total of 128 outstations distributed across four loops, in any configuration required. Outstations can be allocated freely across the loops or 16 radials to suit the site layout.
- 5" full colour TFT display
 - Customisable outstation layout
 - Active call list
 - Live faults view
 - Time & date stamp activity & fault logs
 - Self-describing faults
 - Individual icon per outstation type
 - Two lines of free text fields per outstation
- Delayed call output

- Interface to third party equipment
- Interface to remote lamp buzzer
- Networkable via copper or fibre
- Up to 4 way conference call (Type A/C outstations only) plus operator
- Paging option
 - Broadcast to the loudspeaker of all 'occupied' refuge outstations and all telephones
- Outstation call option (Telephone outstations only)
- Fully monitored

SPECIFICATIONS:

Product code	OCCPLS
Power supply	85-264VAC
Power consumption	320W
Humidity range	95% non-condensing
Temperature range	-5°C to +40°C
Indicators	5" TFT plus fault LEDs
Finish	RAL 9005
Dimensions mm W x H x D	430 x 847 x 190
Bezel dimensions mm	470 x 887
Bezel cutout mm	440 x 857
Knockouts	20mm x 30 (Top)



BALDWIN BOXALL
 LEADING THE WAY TO SAFETY

Baldwin Boxall Communications Ltd
 Wealden Industrial Estate, Farningham Road,
 Crowborough, East Sussex, TN6 2JR, United Kingdom
 T: +44 (0) 1892 664422
 E: hello@baldwinboxall.co.uk
 W: www.baldwinboxall.co.uk

*Protected by UK Patent – GB26051525
 Additional Patent Pending – EP4302472